

Uponor Vario B by-pass WGF XL900 G1/2

1009120

- Made of brass and plastic



About Uponor Vario B by-pass WGF

Specification

- Made of brass
- With integrated valves
- Connection right or left with flat sealing supply
- With lockshield valve or flowmeter for balancing and shutoff
- no primary connection to combine it with the correct accessories
- Loop connection G3/4" eurocone
- Loop distance 50 mm
- Bracket distance 210 mm

Application

- For underfloor heating and cooling
- Combineable with actuators FT 30x1,5
- Max. pressure: 6 bar at 60°C

Uponor Vario B by-pass WGF XL900 G1/2

1009120



Status

Item Available Till date 2028-12-31T00:00:00.000+0100

Product code

Item no EAN	7318793556905
Item no GTIN	07318793556905
Item no LVI	2025082
Item no NOBB	41947477
Item no NRF	8362456
Item no RSK	2418549
Item no VVS	046259034

Dimensions

Item Unit Height	50
Item Unit Length	200
Item Unit Weight	0,496
Item Unit Width	110
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905434534
Packaging GTIN PL3	064149054445080
Packaging Height PL1	50
Packaging Height PL3	200
Packaging Length PL1	200
Packaging Length PL3	255
Packaging Quantity PL1	1
Packaging Quantity PL3	5
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Volume PL1	0,0011

Packaging Volume PL3	0,00714
Packaging Weight PL1	0,506
Packaging Weight PL3	2,63
Packaging Width PL1	110
Packaging Width PL3	140

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb