

Uponor FPL-X compression adapter 20x2,0-G3/4"

1009196

- Fits 3/4" fittings
- Includes insert, nut, and compression ring



About Uponor FPL-X compression adapter

Specification

- Compression fittings for Uponor PE-Xa pipes
- Made of dezincification-resistant (DR) brass
- Available with BSP, metric and eurocone-compatible connections
- Variants for WGF, Vario B and other manifold types
- Plated versions available for visible on-wall installations

Application

- Connection of Uponor PE-Xa pipes to manifolds and radiator valves
- Use in hot and cold water distribution systems
- Radiator connections with visible or concealed installations
- Adaptation of PE-Xa pipes to BSP and metric threaded interface

Uponor FPL-X compression adapter 20x2,0-G3/4"

1009196



Measurements

Cylindric_thread_G	0,75
LENGTH_L	27,7
Length (I1)	18,7
Length (I2)	9
Wall thickness_s	2,0

Product code

Item no EAN	7318792946707
Item no GTIN	07318792946707
Item no LVI	2026004
Item no NOBB	41946686
Item no NRF	8362169
Item no RSK	2417905
Item no VVS	045179820

Dimensions

Item Unit Height	25
Item Unit Length	30
Item Unit Weight	0,08
Item Unit Width	30
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905434688
Packaging GTIN PL3	06414905445134
Packaging Height PL1	35
Packaging Height PL3	100
Packaging Length PL1	30
Packaging Length PL3	350
Packaging Quantity PL1	1
Packaging Quantity PL3	50

Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Volume PL1	0,0000315
Packaging Volume PL3	0,006125
Packaging Weight PL1	0,085
Packaging Weight PL3	4,58
Packaging Width PL1	30
Packaging Width PL3	175

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb