

## Uponor Vario PLUS flowmeter 4 l/min

1009217

- With shut-off function



### About Uponor Vario PLUS flowmeter

#### Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

#### Application

- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

#### Certification

- CE

## Uponor Vario PLUS flowmeter 4 l/min

1009217



### Technical data

Item no EAN	4016203841872
Item no GTIN	04016203841872
Item no VVS	087604107
RSK no.	2418982
Item no NRF	8362672
Item no LVI	2025708
Item (unit of measurement)	pce
Length (l)	146 mm
Length (l1)	74 mm
Packaging Quantity 1	1
Packaging Quantity 3	20
Packaging GTIN PL1	06414905256068
Packaging GTIN PL3	06414905256075
Item Unit Height	150 mm
Item Unit Weight	0,044 kg
Item Unit Width	20 mm

### Technical documents

Download documents here

#### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E enquiries.uk@uponor.com

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)