Product data sheet



GF Uponor MLC bending spring inside 20

1013734

- Bending spring for Uponor Uni-Pipe PLUS and MLC pipes.
- For heating pipe systems



About GF Uponor MLC bending spring inside

Specification

- Oxygen diffusion resistant multi-layer composite pipe(PE-RT - adhesive - longitudinally welded aluminium - adhesive - PE-RT)
- Fire classification E according to EN 13501-1.
- With pipe end caps as hygienic seal according EN 806.

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

GF Uponor MLC bending spring inside 20

1013734



Product code

Item no EAN	4021598700932
Item no GF	35001013734
Item no GTIN	04021598700932
Item no LVI	1725954
Item no NOBB	41942206
Item no NRF	5071835
Item no RSK	1873300
Item no VVS	045498620

Dimensions

Item Unit Height	7
Item Unit Length	620
Item Unit Weight	0,33
Item Unit Width	7
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905538102
Packaging GTIN PL3	06414905483518
Packaging Height PL1	29
Packaging Height PL3	210
Packaging Length PL1	180
Packaging Length PL3	700
Packaging Material (number) PL1	20
Packaging Material PL1	Corrugated fibreboard
Packaging Material (short) PL1	PAP
Packaging Quantity PL1	1
Packaging Quantity PL3	75
Packaging Type PL1	Piece

Packaging Type PL3	Box
Packaging Volume PL1	0,0009396
Packaging Volume PL3	0,03087
Packaging Weight PL1	0,33
Packaging Weight PL3	25,456
Packaging Width PL1	180
Packaging Width PL3	210

Technical data

Recycling Text Block PL1	Corrugated fibreboard

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+