Product data sheet



GF Uponor S-Press tool set A

1013782

- Tool kit consists of:
- UPONOR MLC PIPE CUTTING TOOL 25-63
- UPONOR MLC BENDING SPRING OUTSIDE 16
- UPONOR S-PRESS JAW UPP1 16
- UPONOR S-PRESS JAW UPP1 20
- UPONOR S-PRESS JAW UPP1 25
- UPONOR SPI S-PRESS TOOL CASE
- UPONOR MLC BENDING SPRING OUTSIDE 20
- UPONOR MLC BENDING SPRING OUTSIDE 25
- UPONOR MLC PIPE CUTTING TOOL 14-25
- UPONOR MULTI PIPE & CONDUIT CUTTING TOOL 12-25
- UPONOR MULTI PIPE CUTTING TOOL 25-63



About GF Uponor S-Press tool set A

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press tool set A

1013782



Product code

Item no EAN	4021598727915
Item no GTIN	04021598727915

Dimensions

Item Unit Height	540
Item Unit Length	430
Item Unit Weight	17,6
Item Unit Width	200
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905257928
Packaging Height PL1	540
Packaging Length PL1	430
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,04644
Packaging Weight PL1	17,776
Packaging Width PL1	200

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+