Product data sheet



GF Uponor MLC pipe cutting tool disk 63-110

1014320

- for MLC pipes



About GF Uponor MLC pipe cutting tool disk

Specification

- Oxygen diffusion resistant multi-layer composite pipe(PE-RT - adhesive - longitudinally welded aluminium - adhesive - PE-RT)
- Fire classification E according to EN 13501-1.
- With pipe end caps as hygienic seal according EN 806.

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

GF Uponor MLC pipe cutting tool disk 63-110

1014320



Product code

Item no EAN	4021598111585
Item no GF	35001014320
Item no GTIN	04021598111585
Item no VVS	045498635

Dimensions

Item Unit Height	6
Item Unit Length	41
Item Unit Weight	0,014
Item Unit Width	41
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900453912
Packaging Height PL1	12
Packaging Length PL1	120
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,0001008
Packaging Weight PL1	0,016
Packaging Width PL1	70

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+