


Uponor S-Press tee 14-14-14

1014886

- Made of tin-plated brass
- Contoured Aluminium-sleeve with inspection windows
- Fast 3-step installation (press without bevel)
- Colour coded, breakaway press indicator



About Uponor S-Press tee

Specification

- Tin-plated brass or PPSU
- With fixed press sleeve
- Stop ring
- Colour code
- Test safety
- Male and female threads to BS EN 10226-1

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification


UK Reg4 approval

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor S-Press tee 14-14-14

1014886



Product code

Item no EAN 4021598002098

Item no GTIN 04021598002098

Dimensions

Item Unit Height 50

Item Unit Length 70

Item Unit Weight 0,069

Item Unit Width 25

Item_UOM pce

Measurements

Length (l1) 35

Length (l2) 35

Length (l3) 35

z1 13,7

z2 13,7

z3 13,7

Packaging

Packaging GTIN PL1 06414905435920

Packaging GTIN PL3 06414905445806

Packaging GTIN PL4 06414905489435

Packaging Height PL1 89

Packaging Height PL3 188

Packaging Height PL4 564

Packaging Length PL1 176

Packaging Length PL3 277

Packaging Length PL4 1120

Packaging Quantity PL1 10

Packaging Quantity PL3 80

Packaging Quantity PL4	3840
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,001049488
Packaging Volume PL3	0,009321604
Packaging Volume PL4	0,47249664
Packaging Weight PL1	0,727
Packaging Weight PL3	5,946
Packaging Weight PL4	284,578
Packaging Width PL1	67
Packaging Width PL3	179
Packaging Width PL4	748

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
 WD18 8GA, Watford
 UK

T +44 (0)1923 927000
 E enquiries.uk@uponor.com

www.uponor.com/en-gb