
Product data sheet





GF Uponor S-Press coupling 14-14

1015154

- Made of tin-plated brass
- Contoured Aluminium-sleeve with inspection windows
- Fast 3-step installation (press without bevel)
- Colour coded, breakaway press indicator







About GF Uponor S-Press coupling

Specification

- Tin-plated brass or PPSU
- With fixed press sleeve
- Stop ring
- Colour code
- Test safety
- Male and female threads to BS EN 10226-1

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.


Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.


Certification


UK Reg4 approval
- WRAS or
- KIWA
To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

GF Uponor S-Press coupling 14-14

1015154







Product code

Item no EAN	4021598302884
Item no GF	35001015154
Item no GTIN	04021598302884

Dimensions

Item Unit Height	22
Item Unit Length	55
Item Unit Weight	0,032
Item Unit Width	22
Item_UOM	pce

Measurements

LENGTH_L	54
Length (l1)	21,3
Length (l2)	21,3
z1	11,4

Packaging

Packaging GTIN PL1	06414905436293
Packaging GTIN PL3	06414905446162
Packaging GTIN PL4	06414905489800
Packaging Height PL1	89
Packaging Height PL3	95
Packaging Height PL4	570
Packaging Length PL1	87
Packaging Length PL3	277
Packaging Length PL4	1120
Packaging Quantity PL1	10

Packaging Quantity PL3	80
Packaging Quantity PL4	7680
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000518781
Packaging Volume PL3	0,004710385
Packaging Volume PL4	0,4775232
Packaging Weight PL1	0,339
Packaging Weight PL3	2,812
Packaging Weight PL4	271,584
Packaging Width PL1	67
Packaging Width PL3	179
Packaging Width PL4	748

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+