Product data sheet



GF Uponor S-Press manual tool insert 20

1015780

- Press inserts for manual pressing tool



About GF Uponor S-Press manual tool insert

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press manual tool insert 20

1015780



Product code

Item no EAN	4021598000193
Item no GF	35001015780
Item no GTIN	04021598000193
Item no LVI	1725935
Item no NOBB	41942384
Item no NRF	5071865
Item no RSK	1873358
Item no VVS	045498220

Dimensions

Item Unit Height	20
Item Unit Length	35
Item Unit Weight	0,06
Item Unit Width	28
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905437009
Packaging GTIN PL3	06414905446544
Packaging GTIN PL4	06414905490523
Packaging Height PL1	22
Packaging Height PL3	140
Packaging Height PL4	284
Packaging Length PL1	36
Packaging Length PL3	320
Packaging Length PL4	1200
Packaging Material (number) PL1	4

Packaging Material (number) PL3	20
Packaging Material PL1	Low density polyethylene
Packaging Material PL3	Corrugated fibreboard
Packaging Material (short) PL1	LDPE
Packaging Material (short) PL3	PAP
Packaging Quantity PL1	1
Packaging Quantity PL3	50
Packaging Quantity PL4	400
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000022968
Packaging Volume PL3	0,010304
Packaging Volume PL4	0,27264
Packaging Weight PL1	0,062
Packaging Weight PL3	3,06
Packaging Weight PL4	49,482
Packaging Width PL1	29
Packaging Width PL3	230
Packaging Width PL4	800

Technical data

Recycling Text Block PL1	Low density polyethylene
Recycling Text Block PL3	Corrugated fibreboard

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+