


Uponor Minitec Y compression adapter 2x9,9-3/4"Euro

1016692

- Made of brass
- 3/4 Eurocone
- For 2 loops



About Uponor Minitec Y compression adapter

Specification

- Minitec underfloor heating system for fixation on solid floors or specified insulation materials
- Designed as sturdy pipe fixing system of minimum height, with integrated pipe laying channels for correct pipe laying distances
- For use with Uponor Minitec PE-Xa pipes 9.9 x 1.1 mm; allowing for straight and diagonal pipe laying
- Fire class E to BS EN 13501-1 (pipe and panels)
- Pipe spacing: Vz 5, 10, 15
- Net surface with overlapping nubs: 0,77m²

Application


- Radiant underfloor heating and cooling
- Very low construction height
- For use with qualified filler materials

Certification

- DIN CERTCO: 7F170-F

Uponor Minitec Y compression adapter 2x9,9-3/4"Euro

1016692



Measurements

Cylindric_thread_G	3/4
LENGTH_L	63,5
Length (l1)	13
Z Measurement b	30
z1	46

Product code

Item no EAN	6414905515851
Item no GF	35001016692
Item no GTIN	06414905515851
Item no LVI	2022147
Item no NOBB	50390253
Item no NRF	8361061
Item no RSK	2434387
Item no VVS	381119039

Dimensions

Item Unit Height	30
Item Unit Length	68
Item Unit Weight	0,2
Item Unit Width	48
Item_UOM	pce

Technical data

Recycling Text Block PL3	Corrugated fibreboard
--------------------------	-----------------------

Packaging

Packaging GTIN PL3	06414905446575
Packaging Height PL3	115
Packaging Length PL3	255
Packaging Material (number) PL3	20

Packaging Material PL3	Corrugated fibreboard
Packaging Material (short) PL3	PAP
Packaging Quantity PL3	50
Packaging Type PL3	Box
Packaging Volume PL3	0,007771125
Packaging Weight PL3	10,279
Packaging Width PL3	265

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb