

## Uponor Ecoflex Thermo Single 90x8,2/200

1018115

- Heating and cooling
- One carrier pipe PE-Xa, SDR 11
- Max. load 6 bar / 80°C
- PEX foam, HDPE casing



### About Uponor Ecoflex Thermo Single

#### Specification

- Heating and Cooling
- PE-Xa carrier pipe with oxygen barrier, SDR 11
- Max. load 6 bar / 80°C
- PEX foam, HDPE casing

#### Application

- Buried services for the transport of heating or cooling water.
- Heating operating temperature 80°C based on BS EN 15632

#### Certification

-

## Uponor Ecoflex Thermo Single 90x8,2/200

1018115



### Measurements

Bending radius M	1,1
Outer Diameter_do	200
Outer Diameter_do1	90
Wall thickness_s1	8,2

### Product code

Item no EAN	6414905200818
Item no GF	35001018115
Item no GTIN	06414905200818
Item no LVI	3010209
Item no NOBB	41945313
Item no NRF	8360515
Item no RSK	2190418
Item no VVS	087807090

### Dimensions

Item Unit Height	200
Item Unit Length	1000
Item Unit Weight	4,2
Item Unit Width	200
Item_UOM	m

### Packaging

Packaging GTIN PL1	06414905437177
Packaging Height PL1	2400
Packaging Length PL1	1400
Packaging Quantity PL1	100
Packaging Type PL1	Coil
Packaging Volume PL1	8,064
Packaging Weight PL1	420

Packaging Width PL1

2400

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)