


Uponor Ecoflex Thermo mini 32x2,9/68

1018133

- Heating and Cooling
- One medium pipe PE-Xa with oxygen barrier, SDR 11
- Max. load 6 bar / 80°C
- PEX foam, HDPE casing



About Uponor Ecoflex Thermo mini

Specification

- Heating and Cooling
- PE-Xa carrier pipe with oxygen barrier, SDR 11
- Max. load 6 bar / 80°C
- PEX foam, HDPE casing

Application


- Buried services for the transport of heating or cooling water.
- Heating operating temperature 80°C based on BS EN 15632

Certification

-

Uponor Ecoflex Thermo mini 32x2,9/68

1018133



Measurements

Bending radius M	0,25
Outer Diameter_do	68
Outer Diameter_do1	32
Wall thickness_s1	2,9

Product code

Item no EAN	6414905203314
Item no GF	35001018133
Item no GTIN	06414905203314

Dimensions

Item Unit Height	68
Item Unit Length	1000
Item Unit Weight	0,55
Item Unit Width	68
Item_UOM	m

Packaging

Packaging GTIN PL1	06414905437351
Packaging Height PL1	1600
Packaging Length PL1	700
Packaging Quantity PL1	200
Packaging Type PL1	Coil
Packaging Volume PL1	1,792
Packaging Weight PL1	110
Packaging Width PL1	1600

Technical documents

Download documents here

www.uponor.com/en-gb