

## Uponor Ecoflex Thermo Pipe Twin 2x50x4,6/200

1018137

- Heating and Cooling
- Two carrier pipes PE-Xa with oxygen barrier, SDR 11
- Max. load 6 bar / 80°C
- Coloured centre profile to identify flow and return lines
- PE-X foam, HDPE casing



### About Uponor Ecoflex Thermo Pipe Twin

#### Specification

- Heating and Cooling
- PE-Xa carrier pipe with oxygen barrier, SDR 11
- Max. load 6 bar / 80°C
- PEX foam, HDPE casing

#### Application

- Buried services for the transport of heating or cooling water.
- Heating operating temperature 80°C based on BS EN 15632

#### Certification

-

## Uponor Ecoflex Thermo Pipe Twin 2x50x4,6/200

1018137



### Measurements

Bending radius M	1
Outer Diameter_do	200
Outer Diameter_do1	50
Outer Diameter_do2	50
Wall thickness_s1	4,6
Wall thickness_s2	4,6

### Product code

Item no EAN	6414905210510
Item no GF	35001018137
Item no GTIN	06414905210510
Item no LVI	3010225
Item no NOBB	41945256
Item no NRF	8360505
Item no RSK	2190413
Item no VVS	087809050

### Dimensions

Item Unit Height	175
Item Unit Length	1000
Item Unit Weight	3,59
Item Unit Width	175
Item_UOM	m

### Packaging

Packaging GTIN PL1	06414905437399
Packaging Height PL1	2400
Packaging Length PL1	1400
Packaging Quantity PL1	100
Packaging Type PL1	Coil

Packaging Volume PL1	8,064
Packaging Weight PL1	359
Packaging Width PL1	2400

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)