


Uponor Ecoflex Aqua Twin 50x6,9-25x3,5/175

1018142

- Warm tap water with circulation
- Two medium pipe PE-Xa, SDR 7,4
- Max. load 10 bar / 70°C
- PEX foam, HDPE casing
- Coloured centre profile to identify supply and return lines



About Uponor Ecoflex Aqua Twin

Specification

- Flexible, pre-insulated, self-compensating plastic pipe system.
- Medium pipe: cross-linked polyethylene (PE-Xa) manufactured to BS EN ISO 15875, natural Coloured, PN 10 (SDR 7,4)
- Insulating material: Permanently elastic closed-cell PE-X foam.
- Casing pipe: UV stabilised, corrugated polyethylene (HDPE)
- Twin pipe: colour coded identification to identify supply and return lines

Application

- Transport of warm tap water for buried installations.
- Tap water operating temperature 70°C based on BS EN ISO 15875
- Malfunction temperature 95°C
- Static verification for heavy traffic load of 60 tons

Certification

- UK Reg4 approval
 - WRAS or
 - KIWA
- To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor Ecoflex Aqua Twin 50x6,9-25x3,5/175

1018142



Measurements

Bending radius M	1
Outer Diameter_do	175
Outer Diameter_do1	50
Outer Diameter_do2	25
Wall thickness_s1	6,9
Wall thickness_s2	3,5

Product code

Item no EAN	4021598111752
Item no GF	35001018142
Item no GTIN	04021598111752
Item no NRF	8360875
Item no RSK	2266163
Item no VVS	087363450

Dimensions

Item Unit Height	175
Item Unit Length	1000
Item Unit Weight	2,73
Item Unit Width	175
Item_UOM	m

Packaging

Packaging GTIN PL1	06414905437443
Packaging Height PL1	2400
Packaging Length PL1	1800
Packaging Quantity PL1	200
Packaging Type PL1	Coil
Packaging Volume PL1	10,368
Packaging Weight PL1	546

Packaging Width PL1

2400

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb