

Uponor Ecoflex Quattro 2x32x2,9-32x4,4-25x3,5/175

1018149

- Heating, and warm tap water with circulation
- Four PE-Xa carrier pipes, SDR 11 and 7,4
- Max. load 6 bar heating 80°C / 10 bar tap water 70°C
- Oxygen tightness to ISO 17455 and DIN 4726 (Heating)
- PEX foam, HDPE casing
- Coloured centre profile to identify supply and return lines



About Uponor Ecoflex Quattro

Specification

- Flexible, pre-insulated, self-compensating plastic pipe system
- Medium pipe: Cross-linked polyethylene (PE-Xa) pipe to BS EN ISO 15875, natural coloured, PN 6 (SDR 11) and PN10 (SDR 7,4)
- Oxygen tightness to ISO 17455 and DIN 4726
- Insulating material: closed-cell PE-X foam, permanently elastic, ageing-resistant
- Casing pipe: Corrugated polyethylene (HDPE)

Application

- Buried services for the transport of heating or cooling water
- Heating operating temperature 80°C based on BS EN 15632
- Tap water operating temperature 70°C to BS EN ISO 15875
- Malfunction temperature 95°C
- Static verification for heavy traffic load of up to 60 tons

Certification

UK Reg4 approval (DHW)

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor Ecoflex Quattro 2x32x2,9-32x4,4-25x3,5/175

1018149



Measurements

Bending radius M	0,8
Outer Diameter_do	175
Outer Diameter_do1	32
Outer Diameter_do2	32
Outer Diameter_do3	25
Wall thickness_s1	2,9
Wall thickness_s2	4,4
Wall thickness_s3	3,5

Product code

Item no EAN	4021598111790
Item no GF	35001018149
Item no GTIN	04021598111790
Item no VVS	087817860

Dimensions

Item Unit Height	175
Item Unit Length	1000
Item Unit Weight	2,78
Item Unit Width	175
Item_UOM	m

Packaging

Packaging GTIN PL1	06414905437474
Packaging Height PL1	2400
Packaging Length PL1	1800
Packaging Quantity PL1	200
Packaging Type PL1	Coil
Packaging Volume PL1	10,368
Packaging Weight PL1	556

Packaging Width PL1

2400

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb