

Uponor Wipex tee G3-G3-G3

1018348

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



About Uponor Wipex tee

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex tee G3-G3-G3

1018348



Technical data

Item (unit of measurement) pce

Item no VVS	087842014
-------------	-----------

Item no LVI	1933080
-------------	---------

Item no NRF	8360703
-------------	---------

Length (l1)	75 mm
-------------	-------

Length (l2)	75 mm
-------------	-------

Length (l3)	75 mm
-------------	-------

Packaging Quantity PL1	1
------------------------	---

Packaging Quantity PL3	3
------------------------	---

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb