

Uponor Wipex tee G3-G3-G3

1018348

- Parallel thread G" with sealing O-ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DZR - dezincification resistant brass



About Uponor Wipex tee

Specification

- Wipex fittings in corrosion-resistant brass, dezincification to BS EN ISO 6509 with stainless steel screw.
- Sizes 25-110mm, O-ring sealing between Wipex coupling and base fitting
- Sizes 125-160mm, threads must be sealed using a suitable sealing medium
- Bolt set for couplers in stainless steel with brass washer
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Thermo HP
- Connection of PE and PE-Xa carrier pipes to couplers
- Parallel G male thread
- Max. operating temperature 95°C

Certification

- UK Reg4 approval
 - WRAS or
 - KIWA
- To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor Wipex tee G3-G3-G3

1018348

**Measurements**

Cylindric_thread_G	3
Length (l1)	75
Length (l2)	75
Length (l3)	75

Product code

Item no EAN	7331541098908
Item no GF	35001018348
Item no GTIN	07331541098908
Item no LVI	1933080
Item no NOBB	48326104
Item no NRF	8360703
Item no RSK	2410625
Item no VVS	087842014

Dimensions

Item Unit Height	111
Item Unit Length	152
Item Unit Weight	2,499
Item Unit Width	220
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905260157
Packaging GTIN PL3	06414905260164
Packaging Height PL1	114
Packaging Height PL3	155
Packaging Length PL1	155
Packaging Length PL3	272
Packaging Quantity PL1	1

Packaging Quantity PL3	3
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Volume PL1	0,00394041
Packaging Volume PL3	0,01054
Packaging Weight PL1	2,517
Packaging Weight PL3	7,731
Packaging Width PL1	223
Packaging Width PL3	250

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb