

Uponor Wipex sleeve G1 1/4-G1 1/4

1018356

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



About Uponor Wipex sleeve

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex sleeve G1 1/4-G1 1/4
1018356



Technical data

Item (unit of measurement)	pce
Item no VVS	087830010
Item no LVI	1936032
Item no NRF	8360681
Length (l)	37 mm
Packaging Quantity PL1	1
Packaging Quantity PL3	25
Packaging Quantity PL4	2400

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb