

Uponor Wipex sleeve G2-G2

1018357

- Parallel thread G" with sealing O-ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DZR - dezincification resistant brass



About Uponor Wipex sleeve

Specification

- Wipex fittings in corrosion-resistant brass, dezincification to BS EN ISO 6509 with stainless steel screw.
- Sizes 25-110mm, O-ring sealing between Wipex coupling and base fitting
- Sizes 125-160mm, threads must be sealed using a suitable sealing medium
- Bolt set for couplers in stainless steel with brass washer
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Thermo HP
- Connection of PE and PE-Xa carrier pipes to couplers
- Parallel G male thread
- Max. operating temperature 95°C

Certification

- UK Reg4 approval
 - WRAS or
 - KIWA
- To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor Wipex sleeve G2-G2

1018357



Measurements

Cylindric_thread_G	2
LENGTH_L	45

Product code

Item no EAN	7331541098793
Item no GF	35001018357
Item no GTIN	07331541098793
Item no LVI	1936050
Item no NOBB	41945854
Item no NRF	8360682
Item no RSK	2410616
Item no VVS	087830012

Dimensions

Item Unit Height	45
Item Unit Length	74
Item Unit Weight	0,413
Item Unit Width	74
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905437870
Packaging GTIN PL3	06414905446698
Packaging Height PL1	48
Packaging Height PL3	145
Packaging Length PL1	77
Packaging Length PL3	250
Packaging Quantity PL1	1
Packaging Quantity PL3	15
Packaging Type PL1	Plastic_Bag

Packaging Type PL3	Box
Packaging Volume PL1	0,000284592
Packaging Volume PL3	0,0050025
Packaging Weight PL1	0,418
Packaging Weight PL3	6,42
Packaging Width PL1	77
Packaging Width PL3	138

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb