


Uponor Wipex flange F25/4-85/G1

1018359

- Parallel thread G" with sealing O-ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DZR - dezincification resistance brass



About Uponor Wipex flange

Specification

- Wipex fittings in corrosion-resistant brass, dezincification to BS EN ISO 6509 with stainless steel screw.
- Sizes 25-110mm, O-ring sealing between Wipex coupling and base fitting
- Sizes 125-160mm, threads must be sealed using a suitable sealing medium
- Bolt set for couplers in stainless steel with brass washer
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Thermo HP
- Connection of PE and PE-Xa carrier pipes to couplers
- Parallel G male thread
- Max. operating temperature 95°C

Certification


UK Reg4 approval

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor Wipex flange F25/4-85/G1

1018359



Measurements

Cylindric_thread_G	1
Outer Diameter_do	115
Z Measurement k	85

Product code

Item no EAN	7331541099295
Item no GF	35001018359
Item no GTIN	07331541099295
Item no LVI	1938125
Item no NOBB	41946115
Item no NRF	8360751
Item no RSK	2410645
Item no VVS	087844025

Dimensions

Item Unit Height	25
Item Unit Length	111
Item Unit Weight	1,245
Item Unit Width	111
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905437894
Packaging GTIN PL3	06414905446711
Packaging Height PL1	28
Packaging Height PL3	155
Packaging Length PL1	114
Packaging Length PL3	272
Packaging Quantity PL1	1
Packaging Quantity PL3	10

Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Volume PL1	0,000363888
Packaging Volume PL3	0,01054
Packaging Weight PL1	1,251
Packaging Weight PL3	12,636
Packaging Width PL1	114
Packaging Width PL3	250

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb