

Uponor Wipex flange F80/8-160/G3

1018364

- Parallel thread G" with sealing O-ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DZR - dezincification resistance brass



About Uponor Wipex flange

Specification

- Wipex fittings in corrosion-resistant brass, dezincification to BS EN ISO 6509 with stainless steel screw.
- Sizes 25-110mm, O-ring sealing between Wipex coupling and base fitting
- Sizes 125-160mm, threads must be sealed using a suitable sealing medium
- Bolt set for couplers in stainless steel with brass washer
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Thermo HP
- Connection of PE and PE-Xa carrier pipes to couplers
- Parallel G male thread
- Max. operating temperature 95°C

Certification

UK Reg4 approval

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor Wipex flange F80/8-160/G3

1018364

**Measurements**

Cylindric_thread_G	3
Outer Diameter_do	200
Z Measurement k	160

Product code

Item no EAN	7331541099349
Item no GF	35001018364
Item no GTIN	07331541099349
Item no LVI	1938180
Item no NOBB	41946164
Item no NRF	8360756
Item no RSK	2410650
Item no VVS	087844080

Dimensions

Item Unit Height	28
Item Unit Length	200
Item Unit Weight	4,183
Item Unit Width	200
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905437948
Packaging GTIN PL3	06414905446766
Packaging Height PL1	30
Packaging Height PL3	155
Packaging Length PL1	202
Packaging Length PL3	255
Packaging Quantity PL1	1
Packaging Quantity PL3	3

Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Volume PL1	0,00122412
Packaging Volume PL3	0,01067175
Packaging Weight PL1	4,198
Packaging Weight PL3	12,746
Packaging Width PL1	202
Packaging Width PL3	270

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb