Product data sheet



GF Uponor Uni-C screw valve 35°

1020248

- Relacement isolation valve for Uni-C manifolds



About GF Uponor Uni-C screw valve

Specification

- Modular brass manifold system with male threaded connections
- Components made of tin-plated or plated brass; brackets in galvanised steel
- Compatible with ½" Uni-C compression adapters for MLC and Uni Pipe PLUS pipes
- Thread standards according to EN ISO 228-1 / DIN
- System includes manifolds, valves, end caps, plugs, brackets, couplings, and adapters

Application

- Distribution and connection of tap water
- Manifold-based installations with male threaded connections
- Adaptation between Uponor pipe systems (Uni Pipe PLUS, MLC) and Uponor ½" threaded components
- Use in residential and light commercial installations
- Flexible system extension via manifolds, adapters, and accessories

GF Uponor Uni-C screw valve 35°

1020248



Product code

Item no EAN	6414905516100
Item no GTIN	06414905516100

Dimensions

Item Unit Height	45
Item Unit Length	25
Item Unit Weight	0,046
Item Unit Width	25
Item_UOM	pce

Status

MTO (longer delivery times)	Item available on request, minimum lead time 2 weeks

Packaging

Packaging GTIN PL1	06414905438464
Packaging Height PL1	83
Packaging Length PL1	171
Packaging Quantity PL1	10
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,001873476
Packaging Weight PL1	0,465
Packaging Width PL1	132

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+