

Uponor Uni-C screw valve 35deg

1020248



About Uponor Uni-C screw valve

Specification

- Modular brass manifold system with male threaded connections
- Components made of tin-plated or plated brass; brackets in galvanised steel
- Compatible with ½" Uni-C compression adapters for MLC and Uni Pipe PLUS pipes
- Thread standards according to EN ISO 228-1 / DIN
- System includes manifolds, valves, end caps, plugs, brackets, couplings, and adapters

Application

- Distribution and connection of tap water
- Manifold-based installations with male threaded connections
- Adaptation between Uponor pipe systems (Uni Pipe PLUS, MLC) and Uponor ½" threaded components
- Use in residential and light commercial installations
- Flexible system extension via manifolds, adapters, and accessories

Uponor Uni-C screw valve 35deg

1020248

**Product code**

Item no EAN 6414905516100

Item no GTIN 06414905516100

Dimensions

Item Unit Height 45

Item Unit Length 25

Item Unit Weight 0,046

Item Unit Width 25

Item_UOM pce

Status

MTO (longer delivery times) Item available on request, minimum lead time 2 weeks

Packaging

Packaging GTIN PL1 06414905438464

Packaging Height PL1 83

Packaging Length PL1 171

Packaging Quantity PL1 10

Packaging Type PL1 Base_Box

Packaging Volume PL1 0,001873476

Packaging Weight PL1 0,465

Packaging Width PL1 132

Technical documents[Download documents here](#) Blackmoor Lane The Pavilion
WD18 8GA, Watford
UKT +44 (0)1923 927000
E enquiries.uk@uponor.comwww.uponor.com/en-gb