

## Uponor Uni-C screw valve 35deg

1020248

- Replacement isolation valve for Uni-C manifolds



### About Uponor Uni-C screw valve

#### Specification

- Modular brass manifold system with male threaded connections
- Components made of tin-plated or plated brass; brackets in galvanised steel
- Compatible with ½" Uni-C compression adapters for MLC and Uni Pipe PLUS pipes
- Thread standards according to EN ISO 228-1 / DIN
- System includes manifolds, valves, end caps, plugs, brackets, couplings, and adapters

#### Application

- Distribution and connection of tap water
- Manifold-based installations with male threaded connections
- Adaptation between Uponor pipe systems (Uni Pipe PLUS, MLC) and Uponor ½" threaded components
- Use in residential and light commercial installations
- Flexible system extension via manifolds, adapters, and accessories

## Uponor Uni-C screw valve 35deg

1020248



### Product code

Item no EAN 6414905516100

Item no GTIN 06414905516100

### Dimensions

Item Unit Height 45

Item Unit Length 25

Item Unit Weight 0,046

Item Unit Width 25

Item\_UOM pce

### Status

MTO (longer delivery times) Item available on request, minimum lead time 2 weeks

### Packaging

Packaging GTIN PL1 06414905438464

Packaging Height PL1 83

Packaging Length PL1 171

Packaging Quantity PL1 10

Packaging Type PL1 Base\_Box

Packaging Volume PL1 0,001873476

Packaging Weight PL1 0,465

Packaging Width PL1 132

### Technical documents

Download documents here

Blackmoor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E enquiries.uk@uponor.com

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)