

## Uponor Vario PLUS manifold w. valve LS 6x3/4 Euro

1030582



### About Uponor Vario PLUS manifold w. valve

#### Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

#### Application

- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

#### Certification

- CE

Uponor Vario PLUS manifold w. valve LS 6x3/4 Euro

1030582



Technical data

Item (unit of measurement)	set
Item no VVS	087605136
Item no LVI	2025027
Item no NRF	8362716
Packaging Quantity PL1	1
Packaging Quantity PL4	155

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)