

## Uponor Vario PLUS manifold flowmeter FM 4x3/4 Euro

1030584



### About Uponor Vario PLUS manifold flowmeter

#### Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

#### Application

- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

#### Certification

- CE

## Uponor Vario PLUS manifold flowmeter FM 4x3/4 Euro

1030584



### Technical data

Item no EAN	4016203841346
Item no GTIN	04016203841346
Item (unit of measurement)	set
Length (l)	224 mm
Length (l1)	200 mm
Length (l2)	119 mm
Length (l3)	63 mm
Z-measurement b	50 mm
z3	50 mm
Packaging Quantity 1	1
Packaging Quantity 4	135
Packaging GTIN PL1	06414905265022
Packaging GTIN PL4	06414905265039
Item Unit Height	180 mm
Item Unit Weight	1,002 kg
Item Unit Width	45 mm

### Technical documents

[Download documents here](#)

#### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)