

Uponor Vario PLUS manifold flowmeter FM 4x3/4 Euro

1030584

- Modules for Vario PLUS manifold
- With flowmeter



About Uponor Vario PLUS manifold flowmeter

Specification

- Modular fiberglass-reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- Connection right or left with flat sealing, or connection from below with optional elbow set
- Supplied with lockshield (LS) valve for balancing, or supplied with Flowmeter (FM) for balancing
- Shut-off and flow view
- Adjusting ring for balancing without tools
- Prepared are to apply room name labels
- Return with valves and caps, prepared for actuators
- Loop connection G3/4" Eurocone
- Loop pitch 50 mm
- Header pitch 225 mm

Actuator: NC (normally closed) closes without power

Application

- For underfloor heating and cooling
- Compatible with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS manifold flowmeter FM 4x3/4 Euro

1030584



Measurements

Cylindric_thread_G	0,75
LENGTH_L	224
Length (l1)	200
Length (l2)	119
Length (l3)	63
Z Measurement b	50
Z3	50

Product code

Item no EAN	4016203841346
Item no GF	35001030584
Item no GTIN	04016203841346

Dimensions

Item Unit Height	180
Item Unit Length	220
Item Unit Weight	1,002
Item Unit Width	45
Item_UOM	set

Packaging

Packaging GTIN PL1	06414905265022
Packaging GTIN PL4	06414905265039
Packaging Height PL1	182
Packaging Height PL4	1500
Packaging Length PL1	225
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	135
Packaging Type PL1	Base_Box

Packaging Type PL4	Pallet
Packaging Volume PL1	0,00348075
Packaging Volume PL4	1,44
Packaging Weight PL1	1,052
Packaging Weight PL4	167,02
Packaging Width PL1	85
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb