

Uponor Vario PLUS manifold flowmeter FM 6x3/4 Euro

1030585



About Uponor Vario PLUS manifold flowmeter

Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

Application

- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS manifold flowmeter FM 6x3/4 Euro

1030585



Technical data

Item (unit of measurement)	set
Length (l)	324 mm
Length (l1)	300 mm
Length (l2)	119 mm
Length (l3)	63 mm
Z-measurement b	50 mm
z3	50 mm
Packaging Quantity PL1	1
Packaging Quantity PL4	93

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb