

## Uponor Vario PLUS elbow connection 122/42

1032702



### About Uponor Vario PLUS elbow connection

#### Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

#### Application

- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

#### Certification

- CE

## Uponor Vario PLUS elbow connection 122/42

1032702



### Technical data

Item no EAN	4016203841209
Item no GTIN	04016203841209
Item no VVS	087602150
RSK no.	2418964
Item no NRF	8362653
Item no LVI	2026802
Item (unit of measurement)	set
Length (l1)	122 mm
Length (l2)	44 mm
Length (l3)	40 mm
Packaging Quantity 1	1
Packaging Quantity 3	5
Packaging Quantity 4	720
Packaging GTIN PL1	06414905265084
Packaging GTIN PL3	06414905265091
Packaging GTIN PL4	06414905265107
Item Unit Height	40 mm
Item Unit Weight	0,12 kg
Item Unit Width	60 mm

### Technical documents

Download documents here

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E enquiries.uk@uponor.com

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)