
Product data sheet





GF Uponor S-Press elbow 45° PPSU 63-63

1032879

- Fast installation with easy bevel and without calibration
- Inspection windows on press sleeve
- Colour code







About GF Uponor S-Press elbow 45° PPSU

Specification

- Tin-plated brass or PPSU
- With fixed press sleeve
- Stop ring
- Colour code
- Test safety
- Male and female threads to BS EN 10226-1

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.


Certification

UK Reg4 approval
- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

GF Uponor S-Press elbow 45° PPSU 63-63

1032879



Product code

Item no EAN	6414905220786
Item no GF	35001032879
Item no GTIN	06414905220786
Item no LVI	1720116
Item no NOBB	54938966
Item no NRF	5114361
Item no RSK	1896575
Item no VVS	087433163

Dimensions

Item Unit Height	72
Item Unit Length	164
Item Unit Weight	0,385
Item Unit Width	117
Item_UOM	pce

Measurements

Length (l1)	83,4
Length (l2)	83,4
z1	22,5
Z2	22,5

Packaging

Packaging GTIN PL1	06414905281039
Packaging GTIN PL4	06414905281046
Packaging Height PL1	105
Packaging Height PL4	756
Packaging Length PL1	182

Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	192
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00368823
Packaging Volume PL4	0,72576
Packaging Weight PL1	0,485
Packaging Weight PL4	118,12
Packaging Width PL1	193
Packaging Width PL4	800

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+