


Uponor S-Press tee PPSU 75-75-75

1032888

- Fast installation with easy bevel and without need for calibration
- Inspection windows on press sleeve
- Colour code



About Uponor S-Press tee PPSU

Specification

- Tin-plated brass or PPSU
- With fixed press sleeve
- Stop ring
- Colour code
- Test safety
- Male and female threads to BS EN 10226-1

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification


UK Reg4 approval

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor S-Press tee PPSU 75-75-75

1032888



Product code

Item no EAN	6414905220878
Item no GF	35001032888
Item no GTIN	06414905220878
Item no LVI	1720157
Item no NOBB	54939057
Item no NRF	5114371
Item no RSK	1808042
Item no VVS	087442175

Dimensions

Item Unit Height	84
Item Unit Length	215
Item Unit Weight	0,941
Item Unit Width	151
Item_UOM	pce

Measurements

Length (I1)	107,5
Length (I2)	107,4
Length (I3)	107,5
z1	46,6
Z2	46,5
Z3	46,6

Packaging

Packaging GTIN PL1	06414905281299
Packaging GTIN PL4	06414905281305
Packaging Height PL1	105
Packaging Height PL4	756
Packaging Length PL1	224

Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	150
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,0037632
Packaging Volume PL4	0,72576
Packaging Weight PL1	1,061
Packaging Weight PL4	184,15
Packaging Width PL1	160
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb