

Uponor Aqua Pipe natural Aenor PN6, S 63x5,8 5m

1033506

- Operating pressure 6 bar
- Bar



About Uponor Aqua Pipe natural Aenor PN6, S

Specification

- Pipes manufactured from cross-linked polyethylene - PE-Xa acc. BS EN ISO 15875
- Application class 1 & 2 - Hot water supply
- Fire class E according to BS EN 13501-1.
- Conduits manufactured from high density polyethylene

Application

- Hot water services - where the water temperature does not continuously exceed 70°C, maximum design pressure of 6 bar (conditions to class 2 - BS EN ISO 15875-1:2003). The maximum short-term malfunction temperature is 95°C for an accumulative 100 hours over the working life of the system.
- Cold water services <20 °C - where the maximum system pressure does not exceed the maximum operating pressure of 10 bar.
- Uponor Q&E Shrink-fit system can be used for DHW recirculating systems, provided the operating temperatures and pressures do not exceed the maximum conditions detailed under 'Hot water services'

Uponor Aqua Pipe natural Aenor PN6, S 63x5,8 5m

1033506



Product code

Item no EAN	7321500046163
Item no GF	35001033506
Item no GTIN	07321500046163

Dimensions

Item Unit Height	63
Item Unit Length	1000
Item Unit Weight	0,76
Item Unit Width	63
Item_UOM	m

Measurements

Outer Diameter_do	63
Wall thickness_s	5,8

Packaging

Packaging GTIN PL2	06414905265800
Packaging GTIN PL4	06414905265817
Packaging Height PL2	63
Packaging Height PL4	1000
Packaging Length PL2	5000
Packaging Length PL4	5000
Packaging Quantity PL2	5
Packaging Quantity PL4	350
Packaging Type PL2	Bag
Packaging Type PL4	Wooden_Cage
Packaging Volume PL2	0,019845
Packaging Volume PL4	5
Packaging Weight PL2	4
Packaging Weight PL4	300

Packaging Width PL2	63
Packaging Width PL4	1000

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb