


## Uponor Siccus 20 panel EPS 790x1200x30mm

1034347

- UFH installation panels with grooves
- EPS Compressive strength: = 200 kPa



### About Uponor Siccus 20 panel

#### Specification


- Siccus underfloor heating panel system, consists of EPS (HBCD-free) boards acc. EN 13163 with Aluminium heat spreaders.
- Fire class E to BS EN 13501-1
- For installations with pipe c-c 300mm
- For pipe dim 20mm

#### Application

- Radiant underfloor heating and cooling
- For dry-build installations

## Uponor Siccus 20 panel EPS 790x1200x30mm

1034347



### Measurements

Distance center center	300
LENGTH_L	1200
Z Measurement b	790
Z Measurement h	30

### Product code

Item no EAN	7321500030971
Item no GTIN	07321500030971
Item no LVI	2023430
Item no NOBB	41946380
Item no NRF	8362052
Item no RSK	2419500
Item no VVS	339261028

### Dimensions

Item Unit Height	30
Item Unit Length	790
Item Unit Weight	0,83
Item Unit Width	1200
Item_UOM	pce

### Packaging

Packaging GTIN PL1	06414905457601
Packaging GTIN PL4	06414905491827
Packaging Height PL1	160
Packaging Height PL4	945
Packaging Length PL1	1200
Packaging Length PL4	1200
Packaging Quantity PL1	5
Packaging Quantity PL4	25

Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,1536
Packaging Volume PL4	0,9072
Packaging Weight PL1	4,51
Packaging Weight PL4	44,1
Packaging Width PL1	800
Packaging Width PL4	800

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)