

Uponor Vario PLUS thermometer D=40mm

1034524

- Made of polycarbonate
- For mounting at the connection set
- Consists of two click thermometers



About Uponor Vario PLUS thermometer

Specification

- Modular fiberglass-reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- connection right or left with flat sealing or connection from below with optional elbowset
- supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- shut-off and flow view
- adjusting ring for balancing without tools
- prepared places for room name labels
- return with valves and caps, prepared for actuators
- loop connection G3/4" Eurocone
- loop pitch 50 mm
- header pitch 225 mm

Actuator: NC (normally closed) closes without power

Application

- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS thermometer D=40mm

1034524



Product code

Item no EAN	4016203841889
Item no GF	35001034524
Item no GTIN	04016203841889
Item no LVI	2025671
Item no NOBB	42496663
Item no NRF	8362673
Item no RSK	2418983
Item no VVS	087604118

Dimensions

Item Unit Height	15
Item Unit Length	40
Item Unit Weight	0,019
Item Unit Width	40
Item_UOM	set

Packaging

Packaging GTIN PL1	06414905458028
Packaging GTIN PL3	06414905448005
Packaging Height PL1	22
Packaging Height PL3	65
Packaging Length PL1	82
Packaging Length PL3	360
Packaging Quantity PL1	1
Packaging Quantity PL3	20
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Volume PL1	0,00007216
Packaging Volume PL3	0,003042

Packaging Weight PL1	0,069
Packaging Weight PL3	1,43
Packaging Width PL1	40
Packaging Width PL3	130

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb