

Uponor Vario PLUS automatic air vent 3/8"

1038166

- For Vario Manifolds



About Uponor Vario PLUS automatic air vent

Specification

- Modular fiberglass-reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- Connection right or left with flat sealing, or connection from below with optional elbow set
- Supplied with lockshield (LS) valve for balancing, or supplied with Flowmeter (FM) for balancing
- Shut-off and flow view
- Adjusting ring for balancing without tools
- Prepared are to apply room name labels
- Return with valves and caps, prepared for actuators
- Loop connection G3/4" Eurocone
- Loop pitch 50 mm
- Header pitch 225 mm

Actuator: NC (normally closed) closes without power

Application

- For underfloor heating and cooling
- Compatible with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS automatic air vent 3/8"

1038166



Product code

Item no EAN	4021598131125
Item no GF	35001038166
Item no GTIN	04021598131125

Dimensions

Item Unit Height	40
Item Unit Length	75
Item Unit Weight	0,04
Item Unit Width	40
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905266579
Packaging GTIN PL3	06414905266586
Packaging Height PL1	50
Packaging Height PL3	105
Packaging Length PL1	75
Packaging Length PL3	260
Packaging Quantity PL1	1
Packaging Quantity PL3	10
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Volume PL1	0,0001875
Packaging Volume PL3	0,002184
Packaging Weight PL1	0,09
Packaging Weight PL3	0,95
Packaging Width PL1	50
Packaging Width PL3	80

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb