
Product data sheet



GF Uponor S-Press reducer PPSU 40-25

1039941

- Fast installation with easy bevel and without need for calibration
- Inspection windows on press sleeve
- Material: PPSU



About GF Uponor S-Press reducer PPSU

Specification

- Tin-plated brass or PPSU
- With fixed press sleeve
- Stop ring
- Colour code
- Test safety
- Male and female threads to BS EN 10226-1

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.


Certification

UK Reg4 approval
- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

GF Uponor S-Press reducer PPSU 40-25

1039941



Product code

Item no EAN	6414905228799
Item no GF	35001039941
Item no GTIN	06414905228799
Item no LVI	1720698
Item no NOBB	55171253
Item no NRF	5114394
Item no RSK	1899407
Item no VVS	087455140

Dimensions

Item Unit Height	45.73
Item Unit Length	79.5
Item Unit Weight	0,081
Item Unit Width	45.73
Item_UOM	pce

Measurements

LENGTH_L	79,5
Length (l1)	38,9
Length (l2)	28,3
z1	12,3

Packaging

Packaging GTIN PL1	06414905480333
Packaging GTIN PL4	06414905480340
Packaging Height PL1	89
Packaging Height PL4	678
Packaging Length PL1	176

Packaging Length PL4	1200
Packaging Quantity PL1	5
Packaging Quantity PL4	960
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL4	0,65088
Packaging Weight PL1	0,471
Packaging Weight PL4	111,149
Packaging Width PL1	135
Packaging Width PL4	800

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+