
Product data sheet




GF Uponor S-Press reducer PPSU 50-32

1039943

- Fast installation with easy bevel and without need for calibration
- Inspection windows on press sleeve
- Material: PPSU





About GF Uponor S-Press reducer PPSU

Specification

- Tin-plated brass or PPSU
- With fixed press sleeve
- Stop ring
- Colour code
- Test safety
- Male and female threads to BS EN 10226-1

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.


Certification


UK Reg4 approval
- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

GF Uponor S-Press reducer PPSU 50-32

1039943





Product code

Item no EAN	6414905228812
Item no GF	35001039943
Item no GTIN	06414905228812
Item no LVI	1720700
Item no NOBB	55171272
Item no NRF	5114396
Item no RSK	1899409
Item no VVS	087455150

Dimensions

Item Unit Height	55.4
Item Unit Length	79.5
Item Unit Weight	0,109
Item Unit Width	55.4
Item_UOM	pce

Measurements

LENGTH_L	79,5
Length (l1)	38,9
Length (l2)	27,8
z1	12,8

Packaging

Packaging GTIN PL1	06414905480371
Packaging GTIN PL4	06414905480388
Packaging Height PL1	89
Packaging Height PL4	678
Packaging Length PL1	176

Packaging Length PL4	1200
Packaging Quantity PL1	3
Packaging Quantity PL4	1152
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,001049488
Packaging Volume PL4	0,65088
Packaging Weight PL1	0,378
Packaging Weight PL4	169,171
Packaging Width PL1	67
Packaging Width PL4	800

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+