
Product data sheet




GF Uponor S-Press PLUS tee PPSU 20-20-20

1039945

- Material: PPSU





About GF Uponor S-Press PLUS tee PPSU

Specification

- Unique press indicator foil
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour coded
- Fixed press sleeve with inspection windows
- Precise jaw location
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.


Certification


UK Reg4 approval
- WRAS or
- KIWA
to meet the requirements of the Water Supply (Water Fittings) Regulations 1999

GF Uponor S-Press PLUS tee PPSU 20-20-20

1039945







Product code

Item no EAN	6414905228836
Item no GF	35001039945
Item no GTIN	06414905228836
Item no LVI	1720702
Item no NRF	5114398
Item no RSK	1807981
Item no VVS	087440120

Dimensions

Item Unit Height	49.85
Item Unit Length	74
Item Unit Weight	0,039
Item Unit Width	25.7
Item_UOM	pce

Measurements

Length (l1)	37
Length (l2)	37
Length (l3)	37
z1	15,7
Z2	15,7
Z3	15,7

Packaging

Packaging GTIN PL1	06414905288977
Packaging GTIN PL3	06414905635214
Packaging GTIN PL4	06414905288984
Packaging Height PL1	89

Packaging Height PL3	189
Packaging Height PL4	711
Packaging Length PL1	176
Packaging Length PL3	357
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL3	80
Packaging Quantity PL4	1920
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL3	0,018555075
Packaging Volume PL4	0,68256
Packaging Weight PL1	0,429
Packaging Weight PL3	3,952
Packaging Weight PL4	119,848
Packaging Width PL1	135
Packaging Width PL3	275
Packaging Width PL4	800

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+