

Uponor Vario PLUS manifold flowmeter FM 1x3/4 Euro

1042471

- Modules for Vario PLUS manifold
- With flowmeter



About Uponor Vario PLUS manifold flowmeter

Specification

- Modular fiberglass-reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- Connection right or left with flat sealing, or connection from below with optional elbow set
- Supplied with lockshield (LS) valve for balancing, or supplied with Flowmeter (FM) for balancing
- Shut-off and flow view
- Adjusting ring for balancing without tools
- Prepared are to apply room name labels
- Return with valves and caps, prepared for actuators
- Loop connection G3/4" Eurocone
- Loop pitch 50 mm
- Header pitch 225 mm

Actuator: NC (normally closed) closes without power

Application

- For underfloor heating and cooling
- Compatible with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS manifold flowmeter FM 1x3/4 Euro

1042471



Measurements

Cylindric_thread_G	0,75
LENGTH_L	74
Length (l1)	50
Length (l2)	119
Length (l3)	63
Z Measurement b	50
Z3	50

Product code

Item no EAN	4016203841315
Item no GF	35001042471
Item no GTIN	04016203841315

Dimensions

Item Unit Height	180
Item Unit Length	80
Item Unit Weight	0,28
Item Unit Width	75
Item_UOM	set

Packaging

Packaging GTIN PL1	06414905267811
Packaging GTIN PL3	06414905267828
Packaging Height PL1	185
Packaging Height PL3	150
Packaging Length PL1	132
Packaging Length PL3	490
Packaging Quantity PL1	1
Packaging Quantity PL3	10
Packaging Type PL1	Base_Box

Packaging Type PL3	Box
Packaging Volume PL1	0,0010989
Packaging Volume PL3	0,0135975
Packaging Weight PL1	0,33
Packaging Weight PL3	3,35
Packaging Width PL1	45
Packaging Width PL3	185

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb