

Uponor RS lock pin RS2 black

1042921

- Made from high strength PPSU
- Used lock the RS adapters and fittings to the RS base part.



About Uponor RS lock pin

Specification

- Tin-plated brass
- Fixed press sleeve with inspection windows
- Stop ring
- Colour code
- Test safety
- Male and female threads to BS EN 10226-1

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification

UK Reg4 approval

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor RS lock pin RS2 black

1042921



Product code

Item no EAN	4021598106857
Item no GF	35001042921
Item no GTIN	04021598106857
Item no LVI	1720626
Item no NRF	5079072
Item no RSK	1877271
Item no VVS	045459121

Dimensions

Item Unit Height	10
Item Unit Length	175
Item Unit Weight	0,003
Item Unit Width	5
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905458844
Packaging GTIN PL4	06414905492312
Packaging Height PL1	10
Packaging Height PL4	224
Packaging Length PL1	180
Packaging Length PL4	1200
Packaging Material (number) PL1	4
Packaging Material PL1	Low density polyethylene
Packaging Material (short) PL1	LDPE
Packaging Quantity PL1	10
Packaging Quantity PL4	5000
Packaging Type PL1	Plastic_Bag
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000144
Packaging Volume PL4	0,21504
Packaging Weight PL1	0,04

Packaging Weight PL4	40
Packaging Width PL1	80
Packaging Width PL4	800

Technical data

Recycling Text Block PL1	Low density polyethylene
--------------------------	--------------------------

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb