


Uponor Wipex jointing equal PN10 63x8,6-63x8,6

1042982

- Connection of PE-Xa or PE pipe
- 10 bar, SDR 7,4
- DR = dezincification resistance brass



About Uponor Wipex jointing equal PN10

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application


- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex jointing equal PN10 63x8,6-63x8,6

1042982



Technical data

Item (unit of measurement)	pce
Item no VVS	087882163
Item no LVI	1932112
Item no NRF	8360785
Length (l)	106 mm
Length (l1)	47 mm
Length (l2)	46 mm
Packaging Quantity PL1	1
Packaging Quantity PL3	4
Packaging Quantity PL4	300

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb