


Uponor S-Press elbow 45° PPSU 40-40

1046388

- Fast installation with easy bevel and without calibration
- Inspection windows on press sleeve
- Colour code



About Uponor S-Press elbow 45° PPSU

Specification

- Tin-plated brass or PPSU
- With fixed press sleeve
- Stop ring
- Colour code
- Test safety
- Male and female threads to BS EN 10226-1

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification


UK Reg4 approval

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor S-Press elbow 45° PPSU 40-40

1046388



Product code

Item no EAN	4021598112629
Item no GF	35001046388
Item no GTIN	04021598112629
Item no LVI	1721056
Item no NOBB	48505478
Item no NRF	5071977
Item no RSK	1877962
Item no VVS	087433140

Dimensions

Item Unit Height	47
Item Unit Length	64
Item Unit Weight	0,123
Item Unit Width	64
Item_UOM	pce

Measurements

Length (l1)	55,6
Length (l2)	55,6
z1	16,6
Z2	16,6

Packaging

Packaging GTIN PL1	06414905287536
Packaging GTIN PL4	06414905287543
Packaging Height PL1	89
Packaging Height PL4	570
Packaging Length PL1	176
Packaging Length PL4	1120
Packaging Quantity PL1	5

Packaging Quantity PL4	960
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL4	0,4775232
Packaging Weight PL1	0,654
Packaging Weight PL4	132,538
Packaging Width PL1	135
Packaging Width PL4	748

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb