


Uponor S-Press elbow 45deg PPSU 50-50

1046389

- Fast installation with easy bevel and without calibration
- Inspection windows on press sleeve
- Colour code



About Uponor S-Press elbow 45deg PPSU

Specification

- Tin-plated brass or PPSU
- With fixed press sleeve
- Stop ring
- Colour code
- Test safety
- Male and female threads to BS EN 10226-1

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification


UK Reg4 approval

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor S-Press elbow 45deg PPSU 50-50

1046389



Product code

Item no EAN	4021598112636
Item no GF	35001046389
Item no GTIN	04021598112636
Item no LVI	1721057
Item no NOBB	48505497
Item no NRF	5071978
Item no RSK	1877963
Item no VVS	087433150

Dimensions

Item Unit Height	110
Item Unit Length	54
Item Unit Weight	0,17
Item Unit Width	54
Item_UOM	pce

Measurements

Length (l1)	58,6
Length (l2)	58,6
z1	20
Z2	20

Packaging

Packaging GTIN PL1	06414905287550
Packaging GTIN PL4	06414905287567
Packaging Height PL1	90
Packaging Height PL4	600
Packaging Length PL1	175
Packaging Length PL4	1200
Packaging Quantity PL1	3

Packaging Quantity PL4	576
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00212625
Packaging Volume PL4	0,576
Packaging Weight PL1	0,58
Packaging Weight PL4	134
Packaging Width PL1	135
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb