
Product data sheet




GF Uponor S-Press tee PPSU 40-40-40

1046390

- Fast installation with easy bevel and without need for calibration
- Inspection windows on press sleeve
- Colour code





About GF Uponor S-Press tee PPSU

Specification

- Tin-plated brass or PPSU
- With fixed press sleeve
- Stop ring
- Colour code
- Test safety
- Male and female threads to BS EN 10226-1

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.


Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification

UK Reg4 approval
- WRAS or
- KIWA
To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

GF Uponor S-Press tee PPSU 40-40-40

1046390



Product code

Item no EAN	4021598112643
Item no GF	35001046390
Item no GTIN	04021598112643
Item no LVI	1722248
Item no NOBB	48505516
Item no NRF	5071979
Item no RSK	1877964
Item no VVS	087440140

Dimensions

Item Unit Height	85
Item Unit Length	135
Item Unit Weight	0,19
Item Unit Width	43
Item_UOM	pce

Measurements

Length (l1)	67,6
Length (l2)	67,5
Length (l3)	67,6
z1	28,6
Z2	28,5
Z3	28,6

Packaging

Packaging GTIN PL1	06414905287703
Packaging GTIN PL4	06414905287710
Packaging Height PL1	185

Packaging Height PL4	699
Packaging Length PL1	185
Packaging Length PL4	1200
Packaging Quantity PL1	5
Packaging Quantity PL4	720
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,0031487
Packaging Volume PL4	0,67104
Packaging Weight PL1	1,01
Packaging Weight PL4	161,8
Packaging Width PL1	92
Packaging Width PL4	800

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+