Product data sheet



GF Uponor S-Press chain 75

1046542

- Pressing chain to be used in combination with base unit
- Press Uponor MLC press fittings 63 - 110
- For use with pressing tool UP 110, UP 75 and UP 75 EL



About GF Uponor S-Press chain

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press chain 75

1046542



Product code

Item no EAN	4021598112285
Item no GF	35001046542
Item no GTIN	04021598112285
Item no LVI	1725948
Item no NOBB	48505357
Item no NRF	5071927
Item no RSK	1877982
Item no VVS	045499542

Dimensions

Item Unit Height	60
Item Unit Length	145
Item Unit Weight	2,64
Item Unit Width	135
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905460243
Packaging GTIN PL4	06414905493289
Packaging Height PL1	85
Packaging Height PL4	600
Packaging Length PL1	265
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	72
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet

Packaging Volume PL1	0,00473025
Packaging Volume PL4	0,576
Packaging Weight PL1	3,1
Packaging Weight PL4	223,2
Packaging Width PL1	210
Packaging Width PL4	800

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+