Product data sheet



GF Uponor S-Press base unit for chain 63-110

1046545

- Base unit for the pressing chain to press Uponor MLC press fittings 63 - 110
- For use in combination with pressing tool UP 110, UP 75 and UP 75 EL





About GF Uponor S-Press base unit for chain

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press base unit for chain 63-110

1046545





Product code

Item no EAN	4021598112315
Item no GF	35001046545
Item no GTIN	04021598112315
Item no LVI	1725951
Item no NOBB	48505395
Item no NRF	5071931
Item no RSK	1877985
Item no VVS	045499545

Dimensions

Item Unit Height	50
Item Unit Length	140
Item Unit Weight	2,43
Item Unit Width	130
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905460274
Packaging Height PL1	83
Packaging Length PL1	275
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,00479325
Packaging Weight PL1	2,89
Packaging Width PL1	210

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+