


Uponor S-Press reducer 40-32

1046931

- Made of tin-plated brass
- Fast installation with easy bevel and without need for calibration
- Inspection windows on press sleeve
- Colour code



About Uponor S-Press reducer

Specification

- Tin-plated brass or PPSU
- With fixed press sleeve
- Stop ring
- Colour code
- Test safety
- Male and female threads to BS EN 10226-1

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification


UK Reg4 approval

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor S-Press reducer 40-32

1046931



Status

Item Available Till date

2026-12-31T00:00:00.000+0100

Product code

Item no EAN 4021598114289

Item no GF 35001046931

Item no GTIN 04021598114289

Item no VVS 045480420

Dimensions

Item Unit Height 47

Item Unit Length 85

Item Unit Weight 0,217

Item Unit Width 47

Item_UOM pce

Measurements

LENGTH_L 81,2

Length (l1) 37,9

Length (l2) 30,3

z1 13

Packaging

Packaging GTIN PL1 06414905460717

Packaging GTIN PL4 06414905493524

Packaging Height PL1 89

Packaging Height PL4 570

Packaging Length PL1 135

Packaging Length PL4 1120

Packaging Quantity PL1 5

Packaging Quantity PL4 960

Packaging Type PL1 Base_Box

Packaging Type PL4	Pallet
Packaging Volume PL1	0,001045305
Packaging Volume PL4	0,4775232
Packaging Weight PL1	1,151
Packaging Weight PL4	222,432
Packaging Width PL1	87
Packaging Width PL4	748

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb