


Uponor S-Press coupling 50-50

1046935

- Made of tin-plated brass
- Fast installation with easy bevel and without need for calibration
- Inspection windows on press sleeve
- Colour code



About Uponor S-Press coupling

Specification

- Tin-plated brass or PPSU
- With fixed press sleeve
- Stop ring
- Colour code
- Test safety
- Male and female threads to BS EN 10226-1

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification


UK Reg4 approval

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor S-Press coupling 50-50

1046935



Product code

Item no EAN	4021598114326
Item no GF	35001046935
Item no GTIN	04021598114326
Item no VVS	045480050

Dimensions

Item Unit Height	86
Item Unit Length	53
Item Unit Weight	0,355
Item Unit Width	53
Item_UOM	pce

Measurements

LENGTH_L	88
Length (l1)	37,8
Length (l2)	37,9
z1	12,3

Packaging

Packaging GTIN PL1	06414905401710
Packaging GTIN PL4	06414905401727
Packaging Height PL1	90
Packaging Height PL4	560
Packaging Length PL1	175
Packaging Length PL4	1120
Packaging Quantity PL1	3
Packaging Quantity PL4	576
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00212625

Packaging Volume PL4	0,4691456
Packaging Weight PL1	1,146
Packaging Weight PL4	220,032
Packaging Width PL1	135
Packaging Width PL4	748

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb