Product data sheet



GF Uponor Base thermostat dig. prog. T-26 230V RAL9010

1058425

- In-side port for floor/remote sensor connection
- Fully programmable - 5/2 or 7 day with four heat levels per day
- Multiple control choice - air only, floor only, air and floor
- Holiday mode with override feature
- Optimised start
- Lock facility - tamper proof setting
- Status display on current thermostat mode
- Powered by base unit (Uponor Base controller X-23)
- Optional: remote sensor 1047459 (sold seperately)
- Setpoint range: +5°C - +35°C
- Protection class: IP20
- Colour: RAL9010



About GF Uponor Base thermostat dig. prog. T-26

Specification

- 230V standard wiring
- Common wiring method and controls logic
- Easy integration to standard on/off time control
- Optional: pump logic

Application

- Wired room temperature control for radiant heating

Certification

- CE, UKCA

GF Uponor Base thermostat dig. prog. T-26 230V RAL9010

1058425



Product code

Item no EAN	7321500053413
Item no GF	35001058425
Item no GTIN	07321500053413
Item no LVI	2026913

Dimensions

Item Unit Height	40
Item Unit Length	85
Item Unit Weight	0,14
Item Unit Width	85
Item_UOM	pce

Measurements

LENGTH_L	85
Z Measurement h	40
Z Measurement w	85

Packaging

Packaging GTIN PL1	06414905463220
Packaging Height PL1	73
Packaging Length PL1	114
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,000815556
Packaging Weight PL1	0,24
Packaging Width PL1	98

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+