Product data sheet



GF Uponor Vario ball valve NP G1-G1

1059132

- Made of brass nickel-plated
- Flat sealing connection G1
- 60 mm + length of the manifold



About GF Uponor Vario ball valve

Specification

- Compression fittings with eurocone and metric connections
- Made of brass or tin-plated brass depending on variant
- Compatible with Uponor Uni Pipe PLUS and MLC pipes
- Female and male thread options according to EN ISO 228-1
- No bevel required for installation

Application

For connection of
- drinking water systems
- heating systems
- radiant heating and cooling systems

GF Uponor Vario ball valve NP G1-G1

1059132



Measurements

Cylindric_thread_G	1
Cylindric_thread_G1	1
LENGTH_L	70
Length (l1)	12
Length (l2)	12
Z Measurement h	51
z1	46

Product code

Item no EAN	4021598120549
Item no GF	35001059132
Item no GTIN	04021598120549
Item no LVI	2024328
Item no NRF	8361113
Item no RSK	2987944
Item no VVS	087603108

Dimensions

Item Unit Height	35
Item Unit Length	70
Item Unit Weight	0,95
Item Unit Width	35
Item_UOM	set

Packaging

Packaging GTIN PL1	06414905474905
Packaging GTIN PL3	06414905474912
Packaging GTIN PL4	06414905474929

Packaging Height PL1	44
Packaging Height PL3	100
Packaging Height PL4	1500
Packaging Length PL1	144
Packaging Length PL3	390
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL3	10
Packaging Quantity PL4	1050
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000462528
Packaging Volume PL3	0,006045
Packaging Volume PL4	1,44
Packaging Weight PL1	1
Packaging Weight PL3	10,05
Packaging Weight PL4	1080,25
Packaging Width PL1	73
Packaging Width PL3	155
Packaging Width PL4	800

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+